



Shenzhen Absen Optoelectronic Co., Ltd.

PL2.5 Plus V10- Specifications

Version : V20211206

Parameter		Value
Physical Parameter	LED Type	Black SMD 3in1 1515
	Pixel Pitch (mm)	2.5
	Panel Dimensions (WxHxD)/(mm)	500x500x88
	Pixel Per Panel	200x200
	Panel Weight (kg)	8.6
	Panel Material	Die Casting Aluminum
	Module Dimensions (WxH)/(mm)	250x250
Optoelectronic Parameter	Brightness (nit)	1200
	Refresh Rate (Hz)	3840
	Gray scale (Bit)	15
	Contrast Ratio	8800:1
	Color Temperature (K)	6500
	Viewing Angle (H/V) (°)	160/140
	Driving Type	1/20
	AC Operating Voltage (V)	100 ~ 240
	Power Consumption (Max./Avg.)(W/m ²)	680/230
Application Parameter	Storage Temperature (°C)	-40 ~ +60
	Operating Temperature (°C)	-10 ~ +40
	Storage Humidity (RH)	10% ~ 90%
	Operating Humidity (RH)	10% ~ 90%
	IP Rating (Front/Rear)	IP40/IP21
	Module Maintenance	Front or Rear
	PSU & Others Maintenance	Rear
	Panel Installation Type	Hanging/Stacking
	Max Rigging QTY.	20
	Certificate	ETL,CE,ROHS,FCC

Remark:Power consumption tolerance: $\pm 15\%$, according to the actual situation.