

55" DURASCREEN KX DIGITAL SIGNAGE

Full Sun Outdoor Display

PVO55DSA



The **ProofVision Durascreen KX 55"** is a commercial-grade outdoor digital signage solution built for reliable performance in challenging environments. With a 2500-nit high-brightness panel, IP66-rated enclosure, IK10 impact resistance, and an integrated Android OS, it's ready for seamless integration into AV systems across retail, transport, and public spaces. Its slimline form factor and all-weather durability make it a practical choice for exposed or space-constrained installations, delivering consistent visibility and minimal maintenance over time.

Perfect for

Retail digital signage

Transportation & wayfinding

Hospitality & QSR menus

Smart city messaging

Campus communication

Key Features



Full HD 1080p Resolution

Sharp, high-contrast visuals for content that stands out



Ultra-Bright 2500-nits Display

Readable even in full sunlight



IP66 Weatherproof Enclosure

Dustproof, waterproof, and built to withstand all weather



IK10 Anti-Vandal Protection

Tempered glass resists heavy impact



Integrated Android OS

Easily update content via USB, network, or Wi-Fi



Automatic Brightness Adjustment

Ambient light sensor for optimal visibility and energy savings

24/7

24/7 Operation

Built to run nonstop with a 50,000hour lifespan



Flexible VESA Mounting (500 x 500 mm)

Supports both landscape and portrait installations



For more information Call + 44 (0) 203 4111 693 or email sales@proofvision.co.uk

ProofVision, Unit 1, Avad House, Belvue Road, Northolt, London UB5 5HY

Specification

Specification	
LED Spec	
Panel size	55 inches
Resolution	1920 x 1080 (Full HD)
Brightness	2500 cd/m²
Contrast ratio	5000:1
Viewing angle	178° / 178°
Backlight Type:	Direct LED
Operation Life	50,000 hours
Operation	24/7 continuous
Colour Depth	8-bit
Colour Gamut	72%
Response time	15ms s
Refresh rate	60Hz
Environmental	
Operating temperature	-30°C to 50°C
Impact Rating	IK10
Humidity	5% to 98%
Waterproof rating	IP66
Inputs/Outputs	
HDMI	x 1
USB	x 1
RJ45 Ethernet	x 1
Audio out	x 1 (3.5mm Jack)
Wi-Fi	Yes
Integrated Android System	
OS	Android 12
CPU	Quad-Core ARM Cortex A17, 1.6GHz
GPU	Mali-T764
GI 0	Maii-1704
RAM	2GB DDR3
RAM	2GB DDR3
RAM Storage	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3,
RAM Storage Media Support	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3,
RAM Storage Media Support Power	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP)
RAM Storage Media Support Power Input Voltage	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz
RAM Storage Media Support Power Input Voltage Power Consumption	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz
RAM Storage Media Support Power Input Voltage Power Consumption Physical	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W
RAM Storage Media Support Power Input Voltage Power Consumption Physical Dimensions (W x H x D)	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W
RAM Storage Media Support Power Input Voltage Power Consumption Physical Dimensions (W x H x D) Net Weight	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W 1286 x 757 x 107mm 50kg
RAM Storage Media Support Power Input Voltage Power Consumption Physical Dimensions (W x H x D) Net Weight Mounting	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W 1286 x 757 x 107mm 50kg VESA 500 x 500 mm
RAM Storage Media Support Power Input Voltage Power Consumption Physical Dimensions (W x H x D) Net Weight Mounting Material	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W 1286 x 757 x 107mm 50kg VESA 500 x 500 mm Aluminium with powder-coated finish
RAM Storage Media Support Power Input Voltage Power Consumption Physical Dimensions (W x H x D) Net Weight Mounting Material Colour	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W 1286 x 757 x 107mm 50kg VESA 500 x 500 mm Aluminium with powder-coated finish Black (RAL 9005)
RAM Storage Media Support Power Input Voltage Power Consumption Physical Dimensions (W x H x D) Net Weight Mounting Material Colour Glass	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W 1286 x 757 x 107mm 50kg VESA 500 x 500 mm Aluminium with powder-coated finish Black (RAL 9005) AG-coated tempered glass
RAM Storage Media Support Power Input Voltage Power Consumption Physical Dimensions (W x H x D) Net Weight Mounting Material Colour Glass Orientation	2GB DDR3 8GB eMMC Video (MP4, AVI, RMVB), Audio (MP3, WMA), Images (JPG, PNG, BMP) 110/220V AC, 50/60Hz 250W 1286 x 757 x 107mm 50kg VESA 500 x 500 mm Aluminium with powder-coated finish Black (RAL 9005) AG-coated tempered glass

E&OE PVO55DSA